

Trawersy, wersja nieprzestawna TTS-E

Nośność 1 - 10 t

Długość robocza od 1- 5 m

Rozwiązania inne niż w katalogu są możliwe do wykonania.



Typ	Nośność t	Długość robocza mm	EAN-Nr. 4025092*
TTS 1,0/1000 E	1,0	1.000	*552905
TTS 2,0/1000 E	2,0	1.000	*554534
TTS 3,0/1000 E	3,0	1.000	*552813
TTS 5,0/1000 E	5,0	1.000	*554541
TTS 7,5/1000 E	7,5	1.000	*554558
TTS 10,0/1000 E	10,0	1.000	*554565
TTS 1,0/1500 E	1,0	1.500	*552851
TTS 2,0/1500 E	2,0	1.500	*554572
TTS 3,0/1500 E	3,0	1.500	*552028
TTS 5,0/1500 E	5,0	1.500	*552172
TTS 7,5/1500 E	7,5	1.500	*554589
TTS 10,0/1500 E	10,0	1.500	*554596
TTS 1,0/2500 E	1,0	2.500	*554602
TTS 2,0/2500 E	2,0	2.500	*552769
TTS 3,0/2500 E	3,0	2.500	*552202
TTS 5,0/2500 E	5,0	2.500	*552493
TTS 7,5/2500 E	7,5	2.500	*554619
TTS 10,0/2500 E	10,0	2.500	*554626
TTS 1,0/3500 E	1,0	3.500	*554633
TTS 2,0/3500 E	2,0	3.500	*554640
TTS 3,0/3500 E	3,0	3.500	*552592
TTS 5,0/3500 E	5,0	3.500	*554657
TTS 7,5/3500 E	7,5	3.500	*554664
TTS 10,0/3500 E	10,0	3.500	*554671
TTS 1,0/5000 E	1,0	5.000	*554688
TTS 2,0/5000 E	2,0	5.000	*552523
TTS 3,0/5000 E	3,0	5.000	*554695
TTS 5,0/5000 E	5,0	5.000	*554701
TTS 7,5/5000 E	7,5	5.000	*554718
TTS 10,0/5000 E	10,0	5.000	*554725